









156 ENGINE PISTON

Gudgeon pin housing diameter (mm)			Validity			
20.006 ÷ 20.012			2.0 JTS			
Maximum difference in weight between pistons (g.)			Validity			
± 5			1.8 TS 2.0 JTS [d] 3.2 V6 1.6 TS			
Outer diameter (mm)				Validity		
Category B		Category C		Classe A		
81.930 ÷ 81.940		81.940 ÷ 81.950		81.920 ÷ 81.930		
				1.9 JTD 8v 2.4 JTD 10v		
Piston - cylinder liner play (mm)				Validity		
Category B		Category A		Category C		
0.039 ÷ 0.061		0.038 ÷ 0.058		0.042 ÷ 0.062		
				2.0 JTS		
Piston bush bore (mm)			Validity			
25.999 - 26.004			1.9 JTD 8v			
Piston bush bore (mm)			Validity			
25.999 - 26.004			2.4 JTD 20v			
Piston outer diameter (mm)				Validity		
Category B		Category C		Class A		
82.959 ÷ 82.971		82.969 ÷ 82.978		82.952 ÷ 82.962		
				2.0 JTS		
Outer diameter (mm)				Validity		
Category B		Category C		Classe A		
87.935 - 87.945		87.945 - 87.955		87.925 - 87.935		
				2.5 V6		
Piston bush bore (mm)			Validity			

25.999 - 26.004			2.4 JTD 10v	
Piston outer diameter (mm)			Validity	
Category B	Category A	Category C		
92.915 ÷ 92.925	92.905 ÷ 92.915	92.925 ÷ 92.935	3.2 V6	
Outer diameter (mm) (**)			Validity	
Category B	Category C	Classe A		
81.960 - 81.970	81.968 - 81.978	81.952 - 81.962	1.8 TS 1.6 TS	